

Tango

Soft leather with great seating comfort
Competitive leather in many colours

Particular attributes:

- Soft
- Buffed and embossed furniture leather
- Strong finish
- Practical, smudge-resistant and easy to maintain

Type

Pigmented leather

Comfort

Exceptional seating comfort

Functionality

Comes in a wide array of colours. Can be used for a wide range of purposes and is also ideal for public use



TECHNICAL REPORT

Size: 4.0 - 5.0 m²
Thickness: 0.9 - 1.1 mm

Colour fastness to light: DIN EN ISO 105-B02
Colour fastness to rubbing*: DIN EN ISO 11640
Dry 500 rubs
Wet 80 rubs
Perspiration 50 rubs
Finish adhesion: DIN EN ISO 1644
Tearing load: DIN EN ISO 3377-1
Flexing endurance: DIN EN ISO 5402 (Cracks)
Cigarette + Match test: UNI EN 1021-1 and 2

Requirements	Our test
4	6
4	4-5
4	4-5
4	4-5
1,5	5,58
20	33
20,000	50,000
-	Non-ignition

*Our test result shows the test result on the leather.

Colour fastness to light: The leather will become lighter as time passes. The light fastness indicates how soon this will appear on the leather. The light fastness is measured on a scale from 1 to 8 (1 = lowest and 8 = highest)

Colour fastness to rubbing is measured on a scale from 1 to 5 (1 = lowest and 5 = highest)

Technical specifications on the shade card are guideline only. The information may change due to changes in production. Our website www.sorensenleather.com is at any time updated with current technical specifications.

PCP: According to EU Council Directive 76/769/EEC
AZO dyes: According to EU Council Directive 76/769/EEC
Chrome VI: Our leather does not contain chrome VI

REACH: According to European Community Regulation on chemicals and their safe use (EC 1907/2006)