


lui alto VOLT datasheet

LED ceiling spotlight with flat base, cylindrical head and replaceable optics. Version for mounting on a hollow ceiling box or plastering box; connection to 230V AC/50 Hz mains voltage; dimmable via trailing-edge phase-cut dimmer*.

The lui alto is freely rotatable (with stop) and pivotable by up to 45° on the vertical axis. There are two optics to choose from: The zoom optic, which offers a continuous beam of light that can be set from 20° to 60°, and the lens optic, which has an internal lens combined with various inserts. The optics and optical components can be replaced without any tools, using a simple mechanism. The VOLT light engine is replaceable.

Other versions: lui alto v, lui alto doppio, lui volto (surface-mounted spotlight), lui piano, lui piano v (recessed spotlight)





































technical data lui alto VOLT

properties	material	aluminium, steel chrome-plated, painted or anodised, plastic, glass, optical plastic
	turning range body	360° (with stop)
	movability head	45° (with stop)
	weight	0.85 kg
surface	head	chrome, matt white, matt black
	optic	matt gold, rose gold, bronze, chrome, matt chrome, matt white, matt black
VOLT light engine	average life time	> 40.000 hrs
	energy efficiency class	A
	power	18 W / 13 W*
	color rendering index	perfect color; CRI Ra 97
	color temperature	2700 K, 3000 K
	recommended use	residential and commercial
electricity	dimming	rotary control at the back of the head or external with trailing edge phase-cut dimmer*
	connection	operation at 230 V AC/50 Hz
	permitted operating conditions	max. 30°C for indoor use only



* For a list of compatible dimmers, see www.occhio.de/dim_en ** version chrome



lui alto VOLT overview inserts

	zoom	C 80	C 60	S 80	S 60	S 40	S 30
lui head							
zoom optic							
lens optic							
small lens medium							
small lens high							
soft edge glass							
clear glass							
fresnel lens							
							
	zoom	80°, contour	60°, contour	80°, soft	60°, soft	40°, soft	30°, soft

lui alto VOLT lighting effects





Z20 soft

directed light with soft contour beam angle
(approx. 20°)

inserts: zoom lens
soft edge glass

luminous flux:	perfect color	18 W	690 lm
	perfect color	13 W	550 lm




Z60 soft

directed light with soft contour beam angle
(approx. 60°)

inserts: zoom lens
soft edge glass

luminous flux:	perfect color	18 W	690 lm
	perfect color	13 W	550 lm




C80 contour

directed light with contour beam angle
(approx. 80°)

inserts: lens optic
small lens medium
clear glass

luminous flux:	perfect color	18 W	760 lm
	perfect color	13 W	610 lm





C60 contour

directed light with contour beam angle
(approx. 60°)

inserts: lens optic
small lens high
clear glass

luminous flux:	perfect color	18 W	750 lm
	perfect color	13 W	600 lm

lui alto VOLT lighting effects





S80 soft

directed light with soft contour beam angle
(approx. 80°)

inserts: lens optic
small lens medium
soft edge glass

luminous flux:	perfect color	18 W	750 lm
	perfect color	13 W	600 lm





S60 soft

directed light with soft contour beam angle
(approx. 60°)

inserts: lens optic
small lens high
soft edge glass

luminous flux:	perfect color	18 W	750 lm
	perfect color	13 W	600 lm




S40 soft

directed light with soft contour beam angle
(approx. 40°)

inserts: lens optic
small lens medium
fresnel lens

luminous flux:	perfect color	18 W	630 lm
	perfect color	13 W	510 lm



S30 soft

directed light with soft contour beam angle
(approx. 30°)

inserts: lens optic
small lens high
fresnel lens

luminous flux:	perfect color	18 W	660 lm
	perfect color	13 W	530 lm