


## Sento filo track DALI »cc« datasheet

LED ceiling luminaire with track housing and integrated power supply (driver) for track. Modular LED head-body-system allows free combination of different surfaces of head, body and base. Removable head for configuration and maintenance purposes, LED changeable. Heads available with one sided or double sided light output, power of light source 26 W.

Lighting effect changeable by using optional inserts, dichroic color filters can be added. Adjustment via heat-decoupled carbon pin (fixation of head against rotation optional). External dimmable via DALI.





dimensions in mm

### technical data Sento filo track DALI »cc«

properties	material	aluminium, steel chrome-plated, painted or anodised, plastic, glass, optical plastic	
	length	800 – 1800 mm / 1800 – 2800 mm	
	rotation head	360°	
	movability body	360°	
	weight	1.6 kg	
surface	head	matt gold, rose gold, bronze, chrome, matt chrome, glossy white, matt white, glossy black, matt black	
	body	matt white, matt black, chrome, matt chrome	
	track housing	chrome, glossy white, matt chrome, matt white, glossy black, matt black	
Occhio LED	average life time	> 50.000 hrs	
	energy efficiency class	A+ / A	
	power	26 W	
	color rendering index	perfect color; CRI Ra 97	high flux; CRI Ra 85
	color temperature	2700, 3000 K	3000, 3500, 4000 K
	recommended use	residential and public	public
electricity	dimming	external via DALI	
	power supply unit	integrated, for use with 230 V AC	
	permitted operating conditions	max. 30°C for indoor use only	

## Sento filo track DALI »cc« lighting effects

 head single sided




### Sento B

diffuse light

insert: diffusor glass

luminous flux: perfect color 26 W 1370 lm  
high flux 26 W 1870 lm





### Sento C

directed light  
beam angle approx. 80°

insert: lens

luminous flux: perfect color 26 W 1570 lm  
high flux 26 W 2150 lm





### Sento S40

directed light  
beam angle approx. 40°

insert: spot lens, lens  
soft edge glass

luminous flux: perfect color 26 W 1560 lm  
high flux 26 W 2130 lm



### Sento S30



directed light  
beam angle approx. 30°

insert: spot lens, lens  
fresnel lens

luminous flux: perfect color 26 W 1530 lm  
high flux 26 W 2080 lm

## Sento filo track DALI »cc« lighting effects

 head double sided




### Sento A

diffuse light in both directions

insert: diffuser glass  
diffuser glass

luminous flux: perfect color 26 W 1500 lm  
high flux 26 W 2040 lm





### Sento D

directed light in both directions  
beam angle approx. 80°

insert: lens  
lens

luminous flux: perfect color 26 W 1750 lm  
high flux 26 W 2390 lm



### Sento E

diffuse up light  
directed down light  
beam angle approx. 80°

insert: diffuser glass  
lens

luminous flux: perfect color 26 W 1620 lm  
high flux 26 W 2200 lm