

Sento sospeso trimless »cc« datasheet


LED suspended luminaire with double sided light output, luminous power 2 × 18 W (version with chrome finish 2 × 13 W).
Lighting effect changeable via optional inserts.

trimless-version with height adjustment

LED suspended luminaire freely height adjustable incl. plaster plate for flush mounting on hollow ceiling, connection to constant current source (driver). Extern dimmable (depending on the power supply unit).

trimless-version with fixed length

LED suspended luminaire with fixed height adjustment incl. plaster plate for flush mounting on hollow ceiling, connection to constant current source (driver). Extern dimmable (depending on the power supply unit).




technical data Sento sospeso trimless »cc«

properties	material	aluminium, steel chrome-plated, painted or anodised, plastic, glass, optical plastic	
	freely height adjustable	only variable version	
	length	variable: 500 – 2000 mm / fix: max. 3500 mm	
	weight	variable: 2.4 kg / fix: 1.9 kg	
surface	head	chrome, matt chrome, glossy white, matt white, glossy black, matt black, matt gold	
	base	chrome, matt chrome, glossy white, matt white, glossy black, matt black, matt gold	
Occhio LED	average life time	> 50.000 hrs	
	energy efficiency class	A+ / A	
	power	2 × 18 W max. 2 × 500 mA (> 36 V DC) / 2 × 13 W* max. 2 × 350 mA (> 36 V DC)	
	color rendering index	perfect color; CRI Ra 97	high flux; CRI Ra 85
	color temperature	2700, 3000 K	3000, 3500, 4000 K
	recommended use	residential and public	public
electricity	dimming	with trailing edge phase cut dimmer, push button, DALI or 1–10 V (depends on driver)	
	power supply unit	remote, driven by constant current source max. 2 × 500 mA / 36 V DC	
	permitted operating conditions	max. 30°C for indoor use only	

* version chrome



Sento sospeso trimless »CC« lighting effects




Sento D

directed light in both directions beam angle approx. 80°

inserts: lens
lens

luminous flux:	perfect color	2 × 18 W	2460 lm
	high flux	2 × 18 W	3380 lm
	perfect color	2 × 13 W	1690 lm
	high flux	2 × 13 W	2460 lm



Sento E

diffuse up light directed down light beam angle approx. 80°

inserts: satinised glass
lens

luminous flux:	perfect color	2 × 18 W	2300 lm
	high flux	2 × 18 W	3160 lm
	perfect color	2 × 13 W	1580 lm
	high flux	2 × 13 W	2300 lm