

Sento sospeso trimless datasheet


LED suspended luminaire with double sided light output, luminous power 32 W (version with chrome finish 26 W). Ratio of up and down light adjustable. Lighting effect changeable via optional inserts.

trimless-version with height adjustment

LED suspended luminaire freely height adjustable incl. plaster plate for flush mounting on hollow ceiling, connection to remote constant voltage source (converter). Remote dimmable (depending on power supply unit) or with gestures »touchless fading« on the head.

trimless-version with fixed length

LED suspended luminaire with fixed adjustable height incl. plaster plate for flush mounting on hollow ceiling, connection to remote constant voltage source (converter). Remote dimmable (depending on power supply unit) or with gestures »touchless fading« on the head.



dimensions in mm


technical data Sento sospeso trimless

| | | | |
|-------------|--------------------------------|--|----------------------|
| properties | material | aluminium, steel chrome-plated, painted or anodised, plastic, glass, optical plastic | |
| | freely height adjustable | only variable version | |
| | length | variable: 500 – 2000 mm / fix: max. 3500 mm | |
| | weight | variable: 2.4 kg / fix: 1.9 kg | |
| surface | head | chrome, matt chrome, glossy white, matt white, glossy black, matt black, matt gold | |
| | base | chrome, matt chrome, glossy white, matt white, glossy black, matt black, matt gold | |
| Occhio LED | average life time | > 50.000 hrs | |
| | energy efficiency class | A+ / A | |
| | power | 32 W / 26 W* | |
| | color rendering index | perfect color; CRI Ra 97 | high flux; CRI Ra 85 |
| | color temperature | 2700, 3000 K | 3000, 3500, 4000 K |
| | recommended use | residential and public | public |
| electricity | dimming | »touchless control« and Occhio air (optional) or via trailing-edge phasecut dimmer** (depends on driver) | |
| | power supply unit | remote, driven by constant voltage source 48 V DC / min. 40 W | |
| | permitted operating conditions | max. 30°C for indoor use only | |

* version chrome ** trailing-edge phasecut dimmer and Occhio air not combinable



Sento sospeso trimless lighting effects




Sento D

directed light in both directions beam angle approx. 80°

inserts: lens
lens

| | | | |
|----------------|---------------|------|---------|
| luminous flux: | perfect color | 32 W | 2070 lm |
| | high flux | 32 W | 2920 lm |
| | perfect color | 26 W | 1690 lm |
| | high flux | 26 W | 2300 lm |



Sento E

diffuse up light directed down light beam angle approx. 80°

inserts: satinised glass
lens

| | | | |
|----------------|---------------|------|---------|
| luminous flux: | perfect color | 32 W | 1940 lm |
| | high flux | 32 W | 2730 lm |
| | perfect color | 26 W | 1580 lm |
| | high flux | 26 W | 2150 lm |