

# F12

Swivel armchair with round base in chrome steel, seat upholstered in leather, ecoleather, fabric or custom's fabric.



## Finishing and Materials

### Structure



Chrome

### Coating



**Pix Fabric**  
9 colors



**Mirage Fabric**  
17 colors



**Fenix Wool Fabric**  
15 colors



**Bubble Fabric**  
14 colors



**Hot Fabric**  
14 colors



**Long Life Fabric**  
13 colors



**Velvet Superb**  
18 colors



**Secret Ecoleather**  
22 colors



**Vintage Ecoleather**  
11 colors



**Fiore Leather**  
18 colors



**Vintage Leather**  
4 colors

## Dimensions



Dimension	cm	inch
A	89	35

Dimension	cm	inch
B	47	18.5
C	60	23.6
D	47	18.5

## Volumetric Details

**Weight** 14.5

**Volume** 0.30 mc

**Package** 1

## Gallery



## Downloads

**F12 3D (zip)** - <http://www.midj.com/images/uploads/resources/f12-3d.zip>

## Materials Certifications

### Mirage Fabric

Martindale: 100.000 cycles Composition: 100% Polyester Shrinking about 1% Fire retardant fabric: classe 1IM, B1 DIN 4102, M1, B1 OENORM Part.1, BS 5852 Crib 5, EN 1021, USA Calif. Bull 117, IMO 688 (17) - IMO 563 (14) - IMO 653 (16)

### Fenix Wool Fabric

Martindale: 100.000 cycles Composition: 70% Wool, 25% Polyamid, 5% Fibers Shrinking about: 1% Fire retardant fabric: BS 5852 part. 1, Cigaret test, Match test

### Bubble Fabric

Martindale: 35.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im

### Hot Fabric

Martindale: 45.000 cycles Composition: 100% Pes Fire retardant fabric: BS5852:2006 (p. 11 CRIB 5), EN1021-1, EN1021-2, UNI 9175:2010 - classe 1 im

### Long Life Fabric

Martindale 40.000 cycles Composition: 74% Polyester, 18% Cotton, 8% Acrylic Shrinking about 1%

### Secret Ecoleather

Martindale: 150.000 cycles Composition: 31% Cotton, 48% Polyurethane, 21% Polyester Shrinking about: 1% Fire retardant ecoleather: Classe 1IM, BS 5852 Part. 1, Cigaret Test, Match Test

### Vintage Ecoleather

Ecoleather phtalatic free - R.E.A.C.H. 1907/2006/EU Breathable ecoleather Composition: 90% PVC, 7% Polyurethane, 3% Cotton Shrinking about 1%

### Fiore Leather

BS 5852 parte 1; ISO 5402>50000 cicli; ISO 105B02 ? 5; ISO 3377-1 ?20 N; ISO 11644 ? 2.5 N/Cm; EN 1021/1-2; EN ISO 17233 -20°; IMO RES A 6528(16)

### Vintage Leather

UNI EN ISO 105 B02 ?3; ISO 5402>50000 cicli; ISO 3377-1?20; UNI EN ISO 11640 Secco - Dry 50 c ?4 Umido - Wet 20 c ? 3; Sudore - Sweat 20 c ? 3