



SPURBAMI

Design by Dima Loginoff


Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes.

Typology: SUSPENSION LAMP

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Ceiling cut-out installation
- Supply voltage ~220-240V
- Switch mode: on-off dimmable trailing edge
- Die cast aluminium body, painted
- Opalescent diffuser

Product code composition



URBAN / solo con illuminazione verso il basso / downward lighting only

Type	Article	Colours	Finishing	Source
SP	URBA MI	BC wrinkled white	XX	LED 15W - diffused beam 3000K
		BR matt bronze		
		NI matt nickel		

CE IP20 CRI90 220-240Vac **LED** ~946 lm (*) 63 lm/W (*)

foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

example composition code | SP | URBAMI | BR | XX | LED

Available colors



BC
Wrinkled
white

BR
Matt
bronze

NI
Matt
nickel

CUSTOMER _____ NOTES _____

SPURBAMI_XXLED

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.