



PLUL1160 - recessed
PLUL2160 - recessed
 Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
 Available in several colours and sizes.

Typology: WALL, CEILING

Ratings

- Built in **LED** module
- CCT 3000 K
- Wallward light (wall), downlight or uplight (ceiling)
- Surface installation over holes (legs) and in Ceiling cut-out (recessed canopy)
- Supply voltage ~220-240V
- Switch mode: on-off
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser

kg 23 m³ 0.57

Product code composition

U-LIGHT /plafoniera h10 cm oppure h25 cm, ad incasso - driver NON INCLUSO
 /h10 cm or h25 cm recessed ceiling lamp - driver NOT INCLUDED

Type	Article	Colours	Version	Source
PL	UL 1 160 LED (h10 cm)	AN anthracite grey	IN recessed canopy	LED 108W - diffused beam 3000K
	UL 2 160 LED (h25 cm)	RU rust brown		


CE IP20 CRI90 ~8274 lm 77 lm/W

foro - hole Ø 4,5 cm / profondità min - min depth 10 cm

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).
 Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code | PL | **UL1160LED** | RU | IN |

CEDMWC00202 dimmable 1-10 24VDC driver max 80W (*) x 2 pcs. OPTIONAL




rosone incasso / recessed canopy

hole Ø 4,5 cm

min depth 10cm

4 cm

Ø 6,5 cm



altezze disponibili
available ceiling heights



10 cm
height



25 cm
height

Available colors



AN
Anthracite
grey



RU
Rust brown

CUSTOMER _____ NOTES _____
 PLUL_160LED_ _IN _____

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.