


PL UL 1 160
PL UL 2 160
Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
Available in several colours and sizes.

Typology: WALL, CEILING

Ratings

- Built in **LED** module
- CCT 3000 K
- Wallward light (wall), downlight or uplight (ceiling)
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser




kg 25 m³ 0.57


standard
canopy
Ø 33 cm

Ø 160 cm

rosone standard / standard canopy



altezze disponibili
available ceiling heights



10 cm
height

25 cm
height

Product code composition

U-LIGHT / plafoniera h10 cm oppure h25 cm con rosone / *h10 cm or h25 cm ceiling lamp with canopy*

Type	Article	Colours	Version	Source
PL	UL 1 160 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 108W - diffused beam 3000K
	UL 2 160 LED (h25 cm)	RU rust brown		

CE IP20 CRI90 **LED** ~8274 lm 77 lm/W

Installazione come plafoniera (downlight o uplight) oppure applique (con illuminazione verso la superficie di installazione).
Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code | **PL** | **UL2160LED** | **AN** | **XX** |

Available colors



AN
Anthracite
grey



RU
Rust brown

PLUL_160LED__XX

CUSTOMER _____ NOTES _____

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is estimated based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.